


Pro MagShield



Protected repositionable graphic display system

Our Pro MagShield series is a range of innovative, heavy-duty display solutions that are guaranteed to preserve your graphics and save you time, labour and money. It's impervious to external damage, as it has a scratch resistant design that protects the images from wear & tear.

Our Pro MagShield uses protected printing, which shields the graphics from damage, which prolongs its use and longevity. Not only does our Pro MagShield look good, it can also handle the pressure and challenges of a fast-paced environment.



USP

- Our Pro MagShield is a cost effective solution, guaranteed to save you labour, time and money
- Our Pro MagShield has a scratch resistant design making it ideal for heavy duty use
- Our Pro MagShield is available for print on a wide variety of printers and ink delivery systems
- Our Pro MagShield uses a protected print which makes it even more hard and durable, thus safeguarding your graphics for longer



Applications

- Advertising & Promotion
- In-store & POS
- Displays & Exhibitions
- School, Office, Home

Thickness variation

0.55 - 1.70 mm

Width variation

1600 - 5000 mm

Length variation

20 m / On request



Pro MagShield

Product Description

Our Pro MagShield series is a range of innovative, heavy-duty display solutions that are guaranteed to preserve your graphics and save you time, labour and money. It's impervious to external damage, as it has a scratch resistant design that protects the images from wear & tear. Our Pro MagShield uses protected printing, which shields the graphics from damage, which prolongs its use and longevity. Not only does our Pro MagShield look good, it can also handle the pressure and challenges of a fast-paced environment.

Features

- Graphics perfect for heavy duty or fast-pace environments
- Suitable as a short term graphic system solution
- Protected print
- Scratch resistance

Applications

- Retail & POS
- Commerce, Offices and Schools
- Exhibitions stands
- Indoor/Outdoor application

Advantages

- Impervious to external damage
- Cost-effective solution
- Effortless installation and adjustment
- Printable on a wide range of printers and ink delivery systems

Product Specifications

Pro MagShield	Thickness (mm)	Width (mm)	Length (m)	Magnet (mm)	Adhesive	Ink Compatibility*
Pro MagShield 2	0.90	1000	1.4	0.5	Premium	UV
Pro MagShield 3	0.80	1000	1.4	0.4	Premium	UV
Pro MagShield 4	1.60	1200	On request	0.5	Premium	UV
Pro MagShield 5	1.50	1000	On request	0.4	Premium	UV
Pro MagShield 8	0.70	1250	On request	0.5	None	UV/ES
Pro MagShield 10	0.60	1000	On request	0.4	None	UV/ES
Pro MagShield 12	0.65	1250	On request	0.5	None	UV/ES
Pro MagShield 14	0.55	1000	On request	0.4	None	UV/ES

Ink Compatibility*

UV = UV curable, **ES** = (Eco) Solvent, **L** = Latex

Storage Conditions

- Please preserve it in closed environments, devoid of sunlight
- Shelf life is 12 months and unfinished material should be seal-packed
- Temperature should be kept between 10-35°C
- The relative humidity should be kept between 20-70%

Installation & Handling

- The Pro MagShield should be applied onto a clean surface
- Unfinished material should be used up within one month
- The Pro MagShield works between 10-35°C and humidity between 30-60%
- When applied the temperature change should be within 40°C daily

Cautions

- Excess UV ink piling should be avoided, soft UV ink is recommended
- Actual colours may differ because of material make-up of the Pro MagShield