




## Galvanized steel tape with optional adhesive backing

Our Pro SteelTape is a white coated, galvanized, adhesive backed steel tape that can turn any and all surfaces into magnetically attractive ones. This makes it ideal for use in combination with our Pro MagTape for all sorts of applications, e.g displays, light systems, secondary glazing, and more. It is also widely used and popular when making displays or attaching anti-mosquito nets on windows. Our Pro SteelTape is available in a variety of widths, finishes and with optionable adhesive backing to suit your requirements.



### USP

- It is a cost effective solution for all your display needs
- Our Pro SteelTape is available in a variety of widths
- Suitable for indoor and outdoor application on any steel surface
- Supplied with an adhesive option to suit



### Applications

- Advertising
- Instore & POS
- School, Office, Home
- Exhibitions & Stands

### Thickness variation

0.11 - 0.22 mm

### Width variation

0.11 - 1.50 mm

### Length variation

0.01 - 100 m



# Pro SteelTape

## Product Description

Our Pro SteelTape is a white coated, galvanized, adhesive backed steel tape that can turn any and all surfaces into magnetically attractive ones. This makes it ideal for use in combination with our Pro MagTape for all sorts of applications, e.g displays, light systems, secondary glazing, and more. It is also widely used and popular when making displays or attaching anti-mosquito nets on windows. Our Pro SteelTape is available in a variety of widths, finishes and with optionable adhesive backing to suit your requirements.

## Features

- Practical easy to cut non-adhesive backing
- Adhesive options are available
- Adhesive types include foam and premium TESA
- Some variations can hold and support different types of magnets, including neodymium

## Applications

- Advertising & Promotion
- In-store & POS
- School, Office, Home
- Exhibitions & Stands

## Advantages

- Suitable for indoor and outdoor application on any flat surface

## Product Specifications

| Pro SteelTape    | Thickness (mm) | Width (mm) | Length (m)                              |
|------------------|----------------|------------|---|
| Pro SteelTape 2  | 0.1 - 0.2      | 12.50      | 0.01 - 100 / Specific length on request |
| Pro SteelTape 4  | 0.1 - 0.2      | 19.00      | 0.01 - 100 / Specific length on request |
| Pro SteelTape 6  | 0.1 - 0.2      | 25.00      | 0.01 - 100 / Specific length on request |
| Pro SteelTape 8  | 0.1 - 0.2      | 35.00      | 0.01 - 100 / Specific length on request |
| Pro SteelTape 10 | 0.1 - 0.2      | 50.00      | 0.01 - 100 / Specific length on request |

## Storage Conditions

- Preserved in closed environments, devoid of sunlight
- Unfinished material should be seal-packed
- Temperature should be kept between 10°C and 35°C
- The relative humidity should be kept between 20% and 70%

## Installation & Handling

- Our Pro SteelTape should be applied onto a clean surface
- Ideal in combination with our Pro MagTape for secondary glazing or when applied to an aluminium extrusion

## Cautions

- The width determines whether it can hold and support different types of magnets, including neodymium